

Textstōn TexProtect: SDS7.5 SDS15 SDS30**Surface Defense Sealer**

Textstōn TexProtect SDS 7.5, SDS 15 and SDS 30 are state-of-the art WATERBASED non-yellowing sealers that deeply penetrates into any Textstōn porous plaster finishes such as: Veneciano, Lucido, Marmorino, Palazzo, Antico, Dottinato, Frascati, Classico Lime Paint or extra-porous finishes such as Terra, Tuscany and Kurkarit. **SDS** actually bonds with the substrate creating a long-lasting, breathable, protective barrier against oil, grease, water, mildew, stains and dirt. It will not change the color, the shine, or the feel of the finish. Use on interior or exterior surfaces.

USES: TexProtect SDS may be used on all Textstōn absorbent, porous and extra-porous plaster finishes. It may also be used on all absorbent natural stone and concrete surfaces. TexProtect **SDS** is water-based, environmentally-friendly sealer. It is virtually odorless, non-flammable, non-combustible, non-corrosive and VOC compliant. Its PH balance formula is safe for any absorbent plaster or stone surface.

TexProtect SDS sealer will not etch surfaces such as glass, aluminum, plastic or wood.

Application Procedure: Always test in a small, unnoticeable area to determine ease of use and suitability. Surface must be free of all surface coatings and waxes and must be clean and dry. Apply generously over a completely cure (for 24-48 Hours) and *dry* surface with a paint roller, lamb's wool applicator, sponge, sprayer or Hudson multi-purpose sprayer. Allow **TexProtect SDS Sealer** to soak into the surface let set for five minutes and gently wipe of excess with a white towel to avoid residue. Let set for 1 to 1 ½ hours and repeat the procedure for the second coat. When dry, if any residue remains, remove with plain water and a sponge. If residue is persistent use mild alkaline cleaner and scrub pad to remove. Protect sealed surface from rain or water for 24 hours. Apply in temperatures between 55 and 80 F.

Maintenance: TexProtect **SDS** Sealer should be re-applied as needed between 2-8 years.

Coverage: 250 to 400 sq ft per gallon for two coats, depending on the porosity of the surface and the method of application.

Packaging: Available in Quarts, gallons and 5 gallon buckets.

WARRANTY: Textstōn warrants that **TexProtect** Surface Defense Sealer **SDS**, when used with compatible substrates and according to stated application methods, will retain its protective properties for a period of 2 years from the date of application. Liability, either expressed or implied, is limited solely to the replacement of this product when proven to be defective, and does not include and labor costs or consequential damages. It is the user's responsibility to determine the safety and suitability of the product.

Warning: • **Keep Out of Reach of Children.** • **Keep from freezing**

Harmful if swallowed. If ingested, induce liquids. Do not induce vomiting. For skin contact, wash skin immediately. For eyes, flush immediately with water and obtain prompt medical attention.

VOC > 50 grams/liter

TEXSTŌN
Architectural Surfaces

8025 Deering Avenue • Canoga Park (Los Angeles), CA 91304
800-788-7113 Tollfree • 818-227-4812 Phone • 818-227-4852 Fax

www.Textstōn.com